

# Emacs Keyboard Map v.20061129-01 QWERTY Letter

This is an alpha release. Please be indulgent with errors as I am not an expert with Emacs. Send your comments or corrections to: [emacskbdmap@gmail.com](mailto:emacskbdmap@gmail.com) The copyright notice is just there because I haven't figured out yet how to open-source that document (Creative Commons? Gnu Free Documentation License? GPL?)

© 2006 Sami BEN GRINE

<p>~ <b>M-~</b> not-modified</p> <p>⌘ <b>C-x</b> next-error</p>	<p>! <b>M-!</b> shell-command</p> <p>1 <b>C-x 1</b> delete-other-windows</p>	<p>@ <b>M-@</b> mark-word</p> <p>2 <b>C-x 2</b> split-window-vertically</p>	<p># <b>C-x 3</b></p>	<p>\$ <b>M-\$</b> spell-word</p> <p><b>C-x \$</b> set-selective-display</p> <p>4 <b>C-x 4</b> ctl-x-4-prefix</p>	<p>% <b>M-%</b> query-replace</p> <p>5 <b>C-x 5</b> split-window-horizontally</p>	<p>^ <b>C-x ^</b> enlarge-window</p> <p>6 <b>M-^</b> delete-indentation</p>
<p><b>Esc</b></p>	<p><b>Q</b> <b>C-q</b> quote-insert C-h q no binding <b>C-x q</b> kbd-macro-query <b>C-x C-q</b> toggle-read-only <b>M-q</b> fill-paragraph M-C-q no binding</p>	<p><b>W</b> <b>C-w</b> kill-region <b>C-h w</b> where-is <b>C-x w</b> widen <b>C-x C-w</b> write-file <b>M-w</b> copy-region-as-kill <b>M-C-w</b> append-next-kill</p>	<p><b>E</b> <b>C-e</b> end-of-line C-h e no binding <b>C-x e</b> all-last-kbd-macro <b>C-x C-e</b> eval-last-sexp <b>M-e</b> forward-sentence <b>M-C-e</b> end-of-defun</p>	<p><b>R</b> <b>C-r</b> isearch-backward C-h r no binding <b>C-x r</b> copy-rectangle-to-register <b>C-x C-r</b> find-file-read-only <b>M-r</b> isearch-backward M-C-r no binding</p>	<p><b>T</b> <b>C-t</b> transpose-chars <b>C-h t</b> help-with-tutorial <b>C-x t</b> no binding <b>C-x C-t</b> eval-last-sexp <b>M-t</b> transpose-words <b>M-C-t</b> transpose-sexps</p>	<p><b>Y</b> <b>C-y</b> yank C-h y no binding C-x y no binding C-x C-y no binding M-y no binding <b>M-C-y</b> yank-pop</p>
<p><b>Tab</b></p> <p><b>TAB</b> indent-for-tab-command</p>	<p><b>A</b> <b>C-a</b> beginning-of-line <b>C-h a</b> command-apropos <b>C-x a</b> append-to-buffer <b>C-x C-a</b> add-mode-abbrev <b>M-a</b> backward-sentence <b>M-C-a</b> beginning-of-defun</p>	<p><b>S</b> <b>C-s</b> isearch-forward <b>C-h s</b> describe-syntax C-x s save-some-buffers <b>C-x C-s</b> save-buffer M-s no binding <b>M-C-s</b> isearch-forward-regexp</p>	<p><b>D</b> <b>C-d</b> delete-char <b>C-h d</b> describe-function <b>C-x d</b> dired <b>C-x C-d</b> list-directory <b>M-d</b> kill-word <b>M-C-d</b> down-list</p>	<p><b>F</b> <b>C-f</b> forward-char <b>C-h f</b> describe-function <b>C-x f</b> set-fill-column <b>C-x C-f</b> find-file <b>M-f</b> forward-word <b>M-C-f</b> forward-sexp</p>	<p><b>G</b> <b>C-g</b> cancel-command C-h g no binding <b>C-x g</b> insert-register C-x C-g no binding <b>M-g</b> fill-region M-C-g no binding</p>	<p><b>H</b> <b>C-h</b> help-command <b>C-h C-h</b> help-for-help <b>C-x h</b> mark-whole-buffer <b>C-x C-h</b> inverse-add-mode-abbrev <b>M-h</b> mark-paragraph <b>M-C-h</b> mark-defun</p>
<p><b>Ctrl</b></p>	<p><b>Z</b> <b>C-z</b> suspend-emacs C-h z no binding C-x z no binding <b>C-x C-z</b> suspend-emacs <b>M-z</b> zap-to-char M-C-z no binding</p>	<p><b>X</b> <b>C-x</b> control-X-prefix C-h x no binding <b>C-x x</b> copy-to-register <b>C-x C-x</b> exchange-dot-and-mark <b>M-x</b> execute-extended-command M-C-x no binding</p>	<p><b>C</b> <b>C-c</b> exit-recursive-edit <b>C-h c</b> describe-key-briefly C-x c no binding <b>C-x C-c</b> save-buffers-kill-emacs <b>M-c</b> capitalize-word <b>M-C-c</b> exit-recursive-edit</p>	<p><b>V</b> <b>C-v</b> scroll-up <b>C-h v</b> describe-variable C-h v no binding <b>C-x v</b> find-alternate-file <b>M-v</b> scroll-down <b>M-C-v</b> scroll-other-window</p>	<p><b>B</b> <b>C-b</b> backward-char C-h b no binding <b>C-x b</b> switch-to-buffer <b>C-x C-b</b> list-buffers <b>M-b</b> backward-word <b>M-C-b</b> backward-sexp</p>	<p><b>N</b> <b>C-n</b> next-line <b>C-h C-n</b> view-emacs-news <b>C-x n</b> narrow-to-region <b>C-x C-n</b> set-goal-column M-n no binding <b>M-C-n</b> forward-list</p>

**How to use that map ?** Cut the left and right keyboard maps around the edges; make perforations on both holes near the sides and bring both parts together. Finally, place the unfolded "wings" on top of your keyboard or right below your display.

**How that was done ?** I picked a list of common emacs commands. Many things are not covered there, but there is no reason why we wouldn't add more maps in the future (to describe specific modes, commands or variables). I used Microsoft Powerpoint to make the design but I am very much willing to use an open document format. I wanted to use TeX and postscript initially but it's beyond my skills for that kind of thing.

<p>&amp; <b>C-x &amp;</b></p>	<p>* <b>C-x *</b></p>	<p>( <b>C-x (</b> start-kbd-macro <b>M-(</b> insert-parentheses</p>	<p>) <b>C-x )</b> end-kbd-macro <b>M-)</b> move-past-close-and-reindent <b>C-x 0</b> delete-window</p>	<p>_ <b>C-_</b> undo <b>C-x -</b> inverse-add-global-abbrev <b>M-</b> negative-argument</p>	<p>+ <b>C-x +</b> add-global-abbrev = <b>C-x =</b> what-cursor-position <b>M=</b> what-cursor-position</p>	<p><b>Del</b> <b>DEL</b> delete-backward-char <b>C-x DEL</b> backward-kill-sentence <b>M-DEL</b> backward-kill-word</p>
<p><b>U</b> <b>C-u</b> universal-argument C-h u no binding <b>C-x u</b> advertised-undo <b>C-x C-u</b> uppercase-region <b>M-u</b> uppercase-word <b>M-C-u</b> backward-up-list</p>	<p><b>I</b> <b>C-i</b> no binding C-h i no binding <b>C-x i</b> insert-file <b>C-x C-i</b> no binding <b>M-i</b> tab-to-tab-stop M-C-i no binding</p>	<p><b>O</b> <b>C-o</b> forward-char C-h o no binding <b>C-x o</b> other-window <b>C-x C-o</b> delete-blank-lines <b>M-o</b> no binding <b>M-C-o</b> split-line</p>	<p><b>P</b> <b>C-p</b> previous-line C-h p no binding <b>C-x p</b> narrow-to-page <b>C-x C-p</b> mark-page <b>M-p</b> no binding <b>M-C-p</b> backward-list</p>	<p>{ <b>C-x {</b> shrink-window-horizontally } <b>C-x }</b> enlarge-window-horizontally</p>	<p>[ <b>C-x [</b> backward-paragraph ] <b>C-x ]</b> forward-paragraph <b>M-]</b> forward-paragraph</p>	<p>  <b>M- </b> shell-command-on-region <b>M- </b> delete-horizontal-space <b>M-C- </b> indent-region</p>
<p><b>J</b> <b>C-j</b> no binding C-h j no binding <b>C-x j</b> register-to-point C-x C-j no binding <b>M-j</b> indent-new-comment-line M-C-j no binding</p>	<p><b>K</b> <b>C-k</b> kill-line <b>C-h k</b> describe-key <b>C-x k</b> other-window C-x C-k no binding <b>M-k</b> kill-sentence <b>M-C-k</b> kill-sexp</p>	<p><b>L</b> <b>C-l</b> recenter <b>C-h l</b> view-lossage <b>C-x l</b> count-lines-page <b>C-x C-l</b> downcase-region <b>M-l</b> downcase-word M-C-l no binding</p>	<p>: <b>C-x :</b> set-comment-column ; <b>M-;</b> indent-for-comment</p>	<p>“ <b>M-'</b> abbrev-prefix-mark</p>	<p><b>Enter</b> <b>RET</b> newline <b>LFD</b> newline-and-indent</p>	
<p><b>M</b> <b>C-m</b> no binding <b>C-h m</b> describe-mode <b>C-x m</b> mail C-x C-m no binding <b>M-m</b> back-to-indentation M-C-k no binding</p>	<p>&lt; <b>C-x &lt;</b> scroll-left <b>M-&lt;</b> beginning-of-buffer <b>M-,</b> tags-loop-continue</p>	<p>&gt; <b>C-x &gt;</b> scroll-right <b>M-&gt;</b> beginning-of-buffer <b>C-x &gt;</b> scroll-right <b>M-&lt;</b> beginning-of-buffer</p>	<p>? <b>C-h ?</b> help-for-help / <b>C-x /</b> point-to-register</p>	<p><b>Spc</b> <b>C-SP</b> set-mark-command <b>M-SP</b> just-one-space <b>M-C-SP</b> mark-sexp</p>		

© 2006 Sami BEN GRINE

How to use that map ? Cut the left and right keyboard maps around the edges; make perforations on both holes near the sides and bring both parts together. Finally, place the unfolded "wings" on top of your keyboard or right below your display.